



15" Convertible Open Frame Touch Monitor

Effortless Multi-Touch Experience

Projected Capacitive touch technology provides a smooth, effortless multi-touch experience—identical to many of your favorite mobile touch devices.

Greater Durability

Optically bonded cover glass provides a highly durable surface for longer, trouble-free service life.

Sophisticated Bezel-Free Design

Smooth multi-touch surface across the entire face of the monitor for refined aesthetics and easy cleanability.

Display Details

TPK Model #	K15D-O311
LCD Size /Type	15" TFT - Active Matrix
Active Area	304.1 H x 228.1 V mm
Backlight	WLED
Aspect Ratio	4:3
Native Resolution	1024 x 768
Display Colors	16.2 M
Pixel Pitch	0.297 H x 0.297 V mm
Brightness (typ)	315 cd/m ²
Contrast Ratio	800:1
Hor. Viewing Angle	160°
Vert. Viewing Angle	140°
Response Time	8 ms

Touch Details

Touch Technology	Projected Capacitive
Multi-Touch Input	10 points
Input Method	Finger, Thin Glove
Touch Interface	USB-Type B
Multi-Touch OS Support	Windows, Linux, & Android

Dimensions and Weight

Display (WxHxD)	358.0 x 284.9 x 41.4 mm
Display Weight	Kg
Shipping Weight	Kg

Product Details

Power Supply	12V DC Lockable Connector, 4.16A
Power Consumption	Operating: 16 W Sleep: 2 W Off: 0.5 W
Video Input	Analog VGA, DP, HDMI
Audio Input	None
Mounting Options	VESA Mount, Flush Mount w/ bracket
VESA Pattern	100 x 100 mm
Operating Conditions	0°C to +50°C, Noncondensing 80%
Storage Conditions	-20°C to +60°C, Noncondensing 90%
Agency Approvals	CE, FCC-B, RoHS
Warranty	3 year