



17" Open Frame Touch Monitor

Effortless Multi-Touch Experience

Projected Capacitive touch technology provides a smooth, effortless multi-touch experience—identical to many of your favorite mobile touch devices.

Greater Durability

Optically bonded cover glass provides a highly durable surface for longer, trouble-free service life.

Sophisticated Bezel-Free Design

Smooth multi-touch surface across the entire face of the monitor for refined aesthetics and easy cleanability.

Display Details

TPK Model #	K17B-O301
LCD Size /Type	17" TFT - Active Matrix
Active Area	338.0 H x 270.3 V mm
Backlight	WLED
Aspect Ratio	5:4
Native Resolution	1280 x 1024
Display Colors	16.7 M (6 bits + Hi-FRC)
Pixel Pitch	0.264 H x 0.264 V mm
Brightness (typ)	225 cd/m ²
Contrast Ratio	1000:1
Hor. Viewing Angle	170°
Vert. Viewing Angle	160°
Response Time	5 ms

Touch Details

Touch Technology	Projected Capacitive
Multi-Touch Input	10 points
Input Method	Finger, Thin Glove
Touch Interface	USB-Type B
Multi-Touch OS Support	Windows 7/8/10 & Linux - Native HID
Single-Touch OS Support	All Windows, Linux & Mac OSX

Dimensions and Weight

Display (WxHxD)	369.0 x 307.0 x 47.3 mm
Display Weight	3.6 Kg
Shipping Weight	5.2 Kg

Product Details

Power Supply	12V DC, 2.5A
Power Consumption	Operating: 20 W Sleep: 2 W Off: 1 W
Video Input	Analog VGA, DVI-D
Audio Input	None
Mounting Options	VESA Mount, Side Mounting Holes
VESA Pattern	100 x 100 mm
Operating Conditions	0°C to +40°C, Noncondensing 80%
Storage Conditions	-20°C to +60°C, Noncondensing 90%
Agency Approvals	TUV, CE, UL, CUL, FCC-B, RoHS
Warranty	3 year